

Best copy available

60061-101

01/04/2001

1/4



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Registration Division (7504C)
401 "M" St., S.W.
Washington, D.C. 20460

EPA Reg. Number:

60061-101

Date of Issuance:

JAN 04 2001

NOTICE OF PESTICIDE:
 X Registration
 Reregistration

(under FIFRA, as amended)

Term of Issuance:

Name of Pesticide Product:

Pettit Marine Paint
Horizons Ablative
Antifouling Bottom
Paint 1250 Blue

Name and Address of Registrant (include ZIP Code):

Kop-Coat, Inc.
436 Seventh Avenue
Pittsburgh, PA 15219-1818

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.

2. Make the following label changes:

- a. Revise the EPA Registration Number to read, EPA Reg. No. 60061-101.
- b. Place the appropriate EPA Establishment No. on the product labeling.

Signature of Approving Official:

Marshall Swindell, Product Manager 33,
RMBI, AD

Date:

JAN 04 2001

page 2
EPA Reg. No.

3. Submit two copies of the revised final printed label for the record.

The Confidential Statement of Formula dated July 27th, 2000, is acceptable and complies with PR Notice 91-2.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.


Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobial Division(7505C)

7 3/8 50-439

09/14/99



PETTIT
marine paint

ACCEPTED
with COMMENTS
in EPA Letter I

JAN 0 4

Under the Federal Insecticide, Fungicide, and Rodenticide Act, amended, for the pesticide registered under EPA.

60061-

HORIZONS

ABLATIVE ANTIFOULING BOTTOM PAINT

1250 BLUE

- Multi-Season Protection
- Eliminates Paint Build-Up and Heavy Sanding
- Self-polishing
- High copper content
- Excellent for Fiberglass, Steel or Wood Boats

COMMERCIAL AND NON-COMMERCIAL USE
KEEP OUT OF REACH OF CHILDREN.

WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

NET CONTENTS
1 GALLON (128 FL. OZ.)
3.785 LITERS

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage. Causes skin irritation. Harmful if absorbed through skin. Do not get in eyes or on clothing. Wear protective eye gear, goggles or a face shield. Wash hands before eating, drinking, chewing gum, tobacco or using the toilet. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. Harmful if swallowed or inhaled. Do not breathe vapors, spray mist or sanding dust. Remove contaminated clothing and wash clothing before reuse. Wash thoroughly with soap and water after handling.

FIRST AID

IF SWALLOWED: Call a doctor or get medical attention. Do not induce vomiting or give anything by mouth to an unconscious person. Drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol.

IF IN EYES: Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes. Get medical attention.

ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes or allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS: FLAMMABLE! Keep away from heat, sparks and open flame. Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires, blanket flames with foam, CO2 or dry chemical. Wear MSHA/NIOSH certified breathing equipment.

STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by State and local authorities.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labelling.

Product Description: Pettit Marine Paint Abrasive Ablative Antifouling Bottom Paint is an abrasive antifouling coating designed to polish away at a controlled rate, constantly exposing a fresh surface which provides excellent season long antifouling protection. The high loading of cuprous oxide in the formula enables the paint to perform well in even the most

severe fouling areas. The controlled erosion minimizes coating buildup and keeps underwater surfaces smooth and clean. This product may be applied on fiberglass, wood and properly primed steel boats.

Compatibility: This product may be applied over most aged hard antifouling coatings and over most copper-based ablative antifouling coatings. Old soft antifouling paints must be completely removed before applying this product.

Mixing: This product is heavily loaded with cuprous oxide. As a result of this loading there is a tendency for settling to occur especially if the paint has been on the shelf for several months. It is necessary to thoroughly mix the paint before using. If possible shake the can of paint on a mechanical paint shaker. Before using check the sides and bottom of the can to make sure all the pigment has been mixed in. If mixing is going to be done with a wooden paddle or an electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment, then remix the two parts together thoroughly.

Application Temperatures: 50°F and above.

Application Method: Brush, roller or spray.

Thinner: Thinning this product is not normally required. If thinning is necessary, use Pettit 185 ACP Thinner only. Do not thin more than 10% by volume (12 ounces per gallon), or inadequate paint film thickness may result in premature erosion of the finish.

Coverage: This product covers approximately 400 square feet per gallon.

Number of Coats: For best antifouling protection at least two full coats of this product are recommended for the first years protection. It is a good idea for the first coat to be painted in a different color from the top coats. As the topcoat wears away, the base color will start to show through, signaling that it will soon be time to haul and repaint.

Dry Times:	To recoat	To launch
90°F	3 hours	8 hours
70°F	6 hours	16 hours
50°F	12 hours	24 hours

The above dry times are minimums. This product may be recoated and launched after minimum times shown. There is no maximum dry time before launching.

VOC: Less than 440 g/l unthinned. Less than 480 g/l thinned.

Maintenance Of Antifouling Paint: No antifouling paint can be effective under all conditions of exposure. Man-made pollution and natural occurrences can adversely affect antifouling paint performance. Extreme hot and cold water temperatures, silt, dirt, oil, brackish water and even electrolysis can ruin an antifouling paint. Therefore, we strongly suggest that the bottom of the boat be checked regularly to make sure it is clean and that no growth is occurring. Lightly scub the bottom with a soft brush to remove anything from the antifouling paint surface. Scrubbing is particularly important with boats that are idle for extended periods of time. The self-cleaning nature of the coating is most effective when the boat is used periodically.

PAINT SYSTEMS

The paint systems outlined below contain references to other Pettit products. Please read and understand the label and/or Technical Bulletin for these products as well to ensure that they are used properly. For further guidance, please contact your local Pettit salesman or Pettit Customer Service Department at (800) 221-4466 between the hours of 8:30 a.m. and 4:30 p.m. EST.

Previously Painted Surfaces: If the previous coating is in good condition thoroughly sand with 80 grit production paper and wipe clean with a rag dampened with Pettit 185 ACP Thinner to remove sanding residue. Apply two coats of this product observing the proper dry times. If the previous coating is soft or in poor condition, remove to the bare surface by sanding or using paint and varnish remover. Proceed with the appropriate bare system as described below. Old tin copolymer paints must be removed before applying this product.

Bare Fiberglass: All bare fiberglass, regardless of age, must be thoroughly cleaned using Pettit 95 Fiberglass Dewaxer and clean lint-free rags. Several cleanings may be necessary to ensure complete removal of contaminants. Change rags frequently during the dewaxing/cleaning process to ensure complete removal of contaminants rather than merely smearing them on the surface. New boats must be scrubbed with a detergent and water solution and rinsed with fresh water prior to dewaxing. After the surface has been dewaxed, sand it thoroughly with 80 grit production paper and rewash the sanded surfaces with Pettit 95 Dewaxer or 120 Brushing Thinner to remove sanding residue. Apply two coats of this product observing the proper dry times. If sanding is prohibited, as with certain vinyl-ester gelcoats, or is otherwise impractical, make sure the surface has been completely and thoroughly dewaxed and cleaned with Pettit 95 Fiberglass Dewaxer. Then apply one thin continuous coat of Pettit 6999 Sandless Primer. Topcoat with two coats of this product carefully following the topcoating instructions on the Sandless Primer label.

Bare Wood: Sand the entire surface with 80 grit production paper and wipe clean with a rag dampened with Pettit 185 ACP Thinner. Apply a coat of this product thinned 5% with the Pettit 185 ACP Thinner to penetrate and seal the wood. Fill any open seams with Pettit Seam Compound and allow to dry overnight. Apply two full coats of this product observing the proper dry times.

Steel Hulls, Underwater Metal Parts and Keels: For steel hulls and metal keels, consult Pettit Technical Bulletin TB430 High Build Epoxy Primer for complete priming instructions or consult the Pettit Technical Department or your local Pettit representative. For underwater metal parts, consult Technical Bulletin TB112 Underwater Running Gear Painting Specification for complete priming and application details.

DO NOT USE THIS PRODUCT ON ALUMINUM HULLS OR OUTDRIVES

MEDICAL EMERGENCIES: 1-800-548-0489

An RPM Company